

Product Description:

Use on multi surfaces to stop feeding the corrosion that builds up inside and outside all areas effected by the bleach spraying process. Truck and trailer mounted equipment can be sprayed down at the completion of work to combat corrosion. Pumps, sprayers, hoses and fittings can be flushed, thus stopping premature repairs and replacement. Clean haze and streaks from windows to avoid call back.

A regular spray down with **NEUTRA BLEACH** at days end will neutralize bleach crystals and protect equipment, trailers and vehicles from rapid corrosion.

Directions for Use:

Pre-rinse all surfaces to be treated. Mix 8 -16 oz. with 5 gallons of water for low pressure spray applications. For windows or to spray down equipment. Mix 8-16 oz. per 5 gallon for X-Jet application. Mix 15 to 24oz per 5 gallon for downstream injectors. Rinse lightly.

Do not allow to dry on surfaces, always rinse thoroughly. All products should be tested in an inconspicuous area.

Product Number
53120

Batch Number
101718

Neutra Bleach

Bleach/Sodium Hypochlorite Neutralizer

KEEP OUT OF REACH OF CHILDREN

Do not handle until all safety precautions have been read and understood. Use eye, face, and rubber glove protection when handling these contents. Do not store at temperatures above 120°F. Do not allow to freeze. See side panel for additional precautions.



PRESSURE WASHERS • CHEMICALS

1900 Dickinson Road
DePere, WI 54115
920-337-0109



Warning

Suspected of damaging fertility or the unborn child
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container in conformance with State, Local, and Federal regulations.

Consult S.D.S. for additional safety information.
For Medical Emergency Information call 1-800-535-5053.

Not Regulated by DOT